

**STOCK CHASER™**

**Easily Navigates  
Narrow Aisles**

**Up to 1,000 lb  
Payload Capacity**

**Optional 4- or 6-Step Ladder**

**IDEAL FOR  
HARD-TO-REACH BINS**

This versatile parts picker/stock chaser with an optional 4- or 6-step ladder allows you to easily access and haul inventory between locations, or efficiently perform maintenance tasks.



Body & Chassis	
<b>Frame</b>	Welded steel with powder coat-paint
<b>Body and Finish</b>	Diamond-plate body panels; polyester primer/acrylic
Dimensions	
<b>Overall Length</b>	84.0 in (213 cm)
<b>Overall Width</b>	29.5 in (75 cm)
<b>Overall Height</b>	48.0 in (122 cm) without ladder 78.0 in (198 cm) with 4-step ladder 97.0 in (246 cm) with 6-step ladder
<b>Wheel Base</b>	48.0 in (122 cm)
<b>Rear Wheel Track</b>	24.75 in (63 cm)
<b>Cargo Area</b>	29.0 in W x 48.0 in L (74 cm W x 122 cm L)
<b>Vehicle Load Capacity</b>	1,000 lb (453.6 kg)
Power	
<b>Power Source</b>	24-volt DC
<b>Motor Type</b>	High-efficiency series wound
<b>Horsepower</b>	1.5 hp (1.1 kw) at 2800 rpm
<b>Electrical System</b>	24-volt
<b>Batteries (qty/type)</b>	Four 6-volt, deep cycle
<b>Battery Charger</b>	24 V, 120 VAC on-board, UL/CSA
<b>Speed Controller</b>	Solid-state, 275 amp rated
<b>Drive Train</b>	Motor shaft direct drive
<b>Transaxle</b>	Differential with helical gears
<b>Gear Selection</b>	Dash-mounted forward – neutral – reverse
<b>Rear Axle Ratio</b>	14.78:1
<b>Battery Charger</b>	24 V, 120 VAC on-board, UL/CSA
Performance	
<b>Seating Capacity</b>	1 person
<b>Weight (without batteries)</b>	490 lb (225 kg)
<b>Weight (with batteries)</b>	740 lb (335 kg)
<b>Cargo Deck Load Capacity</b>	750 lb (340 kg)
<b>Ground Clearance</b>	4.0 in (10 cm) at differential
<b>Intersecting Clearance Circle</b>	56.0 in (142 cm)
<b>Outside Clearance Circle</b>	10.5 ft (3.2 m)
<b>Ground Speed</b>	9.0 mph max (14.0 kph max)
<b>Towing Capacity (Draw Bar)</b>	100 lb (45 kg) Normal; 840 lb (380 kg) at stall
Steering & Suspension	
<b>Steering</b>	Direct chain and linkage
<b>Service Brake</b>	Rear wheel mechanical drum
<b>Parking Brake</b>	Automatic parking brake
<b>Tires</b>	4.80 x 8 (load range B)
Other Standard Features	
Horn, on-board 24-volt 120-volt/60hz charger, U.L. "E" Certification, plywood cargo deck	
Factory Installed Modifications	
Foam-filled tires, forward motion indicator, stainless steel cargo deck, galvanized steel cargo deck, CE kit, 4-step or 6-step ladder, portable charger, headlight, hour meter, lift-out battery tray, 250-amp hour batteries, non-standard paint color, rear hitch (pintle or "E"), state of charge meter (LED), U.L. approved "EE" classification	
Accessories	
Counterweight kit, side rail kit	



Back



Side

Specifications subject to change without notice.  
Field installed accessories may require installation charges.

